

11' 2260 Brutus Eagle Pro Service Body
on an 84" CA chassis

Brutus Eagle Pro Features:

Body length – 132" + step bumper

Body width – 95"

Cabinet height – 60"

Cabinet depth – 22"

Cabinet drop – None

Cabinets – Single wall 11 gauge A80 galvaneal steel

Cabinet tops – Double wall 11 gauge A80 galvaneal steel

Cargo bay walls – Double wall 11 gauge A80 galvaneal steel

Wheel wells – Single wall 11 gauge A80 galvaneal steel

Main sills – 2" x 3" steel structural tubing

Cross sills – 2" x 4" x 10 gauge steel channels on 12" centers

Flooring – Double wall 11 gauge A80 galvaneal steel

Doors – Single wall 11 gauge A80 galvaneal steel

Shelving – Galvaneal steel with infinitely adjustable track system

Hinges – Painted stainless steel

Handles – Polished stainless steel

Latching – 3-point stainless steel

Door retainers – Stainless steel door springs

Cabinet pressurization – Dual fan motors with rooftop filters and covers for over pressurizing body to keep out dust, snow, and moisture

Door seals – Rubber bulb seals

Wiring – Watertight electrical relay box with master switches, Weatherpak connectors, and continuous protective loom

Interior lights – Recessed rope lighting for full illumination with no shadows

Exterior floodlights – Bosch 8" halogens with individual switches on lights and master switch, lights can be rotated 360 degrees and tilted 180 degrees

Running Lights – Rubber mounted LED's

Paint protection – Stainless steel bonded to the cabinet fronts and rears

-Stainless steel bonded below each door opening

-Body and frame is fully undercoated

Paint – White PPG Delfleet polyurethane

Brutus Body Specifications

Driver side #1 – 60"H x 56"W x 24"D

2-Vertical aluminum doors

1-Master switch panel

1-Cabinet pressurization system

1-7 drawer tool cabinet with top shelf (30" wide)

1-7 drawer tool cabinet with top shelf (18" wide)

1-Bookshelf

1-Rope lighting

Driver side #2 – 39”H x 47”W x 24”D

- 2-Vertical doors
- 1-Shelf
- 1-Rope lighting

Driver side #3 – 60”H x 29”W x 24”D

- 1-Vertical door
- 1-Crane reinforcement
- 1-Shelf
- 1-Reelcraft ½” x 50’ spring rewind air reel with rear body access through sealed box
- 1-Air regulator, filter, and luber system
- 1-Hook for crane controller and cable (front wall)
- 1-Rope lighting

Passenger side #1 – 60”H x 20”W x 24”D

- 1-Vertical door
- 2-Bottle holders with wear pads (front wall)
- 2-Gear hooks (2 rear wall)
- 1-Aluminum oilfield vent package

Passenger side #2 – 60”H x 36”W x 24”D

- 2-Vertical doors
- 1-Master switch panel
- 1-Cabinet pressurization system
- 3-Shelves
- 1-Rope lighting

Passenger side #3 – 39”H x 47”W x 24”D

- 2-Vertical doors
- 2-Shelves
- 1-Rope lighting

Passenger side #4 – 60”H x 29”W x 24”D

- 1-Vertical door
- 3-Shelves
- 1-Rope lighting

Cargo bay – 132”D x 51”W x 43”H (8” raised roof)

- 1-Sliding aluminum roof system with peaked profile for shedding water and snow, Teflon side sliders, double rear doors with stainless latching. Roof can slide forward from the rear or slide back from the front
- 4-Flush mount d-ring tie downs (5,000 lb capacity each)

Misc. features

1-Steel diamond plate bumper

1-2" receiver hitch with 7 blade plastic plug

1-Pintle hitch provision

1-Back-up alarm

2-Rear mud flaps

2-Aluminum grab handles with rubber grips

4-Bosch 8" rooftop swivel halogen floodlights

1-Spring mounted body sub frame to permit chassis flex on severe off road applications