

**9' 6" Brutus BL48A Aluminum Service Body**  
**For an 60" CA light duty chassis**

Brutus Body Features

Body length – 114" + 7" step bumper

Body width – 96"

Cabinet height – 48"

Cabinet depth – 24"

Cabinet drop – None

Cabinets – 1/8" huck-bolted aluminum

Cargo bay walls – 1/8" aluminum

Wheel wells – 1/8" aluminum

Main sills – 3" x 4" aluminum heavy-wall tubing

Cross sills – 3" x 1/4" aluminum channel

Flooring – 3/16" aluminum diamond plate

Doors – 1/8" aluminum with 1/8" glue bonded aluminum hat section stiffeners

Shelving – 1/8" aluminum that are adjustable in 2" increments

Hinges – Polished stainless steel

Handles – Polished stainless steel

Latching – 3-point stainless steel

Door retainers – Stainless steel door springs that lock into position

Cabinet venting – Bottom venturi's with drain holes to remove moisture build-up

Door seals – Rubber bulb seals that are glued into a u-shaped moulding

Drip mouldings – Glue bonded aluminum gutters that channel water away from the doors

Wiring – Watertight electrical relay box with master switches, Weatherpak connectors, and continuous protective loom

Interior ceiling lights – Individual switches on lights with master switch

Interior door lights - Individual switches on lights with master switch, lights can be swivelled 180 degrees

Exterior floodlights – Bosch 8" halogens with individual switches on lights and master switch, lights can be rotated 360 degrees and tilted 180 degrees

Running Lights – Rubber mounted LED's

Warranty – 3-year structural, 3-year limited paint, and 5-year paint fade

Paint protection – 3M vinyl coatings on cabinet front, bottom, and wheel well edges

-3M rubberized wheel well coating

-Hippo Liner coated bumper

-Aluminum diamond plate bonded to the cabinet fronts

Body finish – Fully body worked for a smooth exterior with no seams or weld joints

Paint – White PPG Delfleet polyurethane

Brutus Body Specifications

Driver side #1 – 48"H x 36"W x 24"D

1-Vertical aluminum door

1-Steel toolbox tray with 500 lb roller bearing sliders and locking latch

1-Aluminum bookshelf

1-Ceiling light

Driver side #2 – 26”H x 42”W x 24”D

- 1-Horizontal aluminum door
- 1-Aluminum shelf
- 1-Ceiling light

Driver side #3 – 48”H x 36”W x 24”D

- 1-Vertical aluminum door
- 1-Crane reinforcement
- 1-Aluminum drip tray with drain hose
- 1-Hook for crane controller and cable (front wall)
- 1-Door light

Passenger side #1 – 48”H x 36”W x 24”D

- 1-Vertical aluminum door
- 2-Bottle holders with wear pads (front wall)
- 3-Gear hooks (1 rear wall, 2 back wall)
- 4-Vertical bar holders with tie down tabs (rear wall)
- 1-Stainless steel vent (above bottles)

Passenger side #2 – 26”H x 42”W x 24”D

- 1-Horizontal aluminum door
- 1-Aluminum shelf
- 1-Ceiling light

Passenger side #3 – 48”H x 36”W x 24”D

- 1-Vertical aluminum door
- 3-Aluminum shelves
- 1-Door light

Cargo bay – 114”D x 48”W x 29”H

- 1-Three piece sliding aluminum roof system with folding rear lid, UHMW slider blocks, and stainless latching
- 1-18” tailgate with plastic covered drop chains, adjustable zinc plated latches, hinges with grease nipples and brass inserts, and grip tape
- 4-Zinc plated rotating d-ring tie downs (6,000 lb capacity each)

Misc. features

- 2-Rear mud flaps
- 2-Aluminum grab handles with rubber grips
- 4-Bosch 8” rooftop swivel halogen floodlights
- 1-7”L smooth aluminum step bumper with Hippo Liner coating
- 2-Horizontal steel bumper vice receivers