<u>11' Brutus DM60AX Aluminum Service Deck</u> For an 86" CA medium duty chassis

Brutus Body Features

<u>Body length</u> $-132" + 7"$ step bumper
Body width – 98"
<u>Cabinet height – 60"</u>
Cabinet depth – 24"
$\overline{\text{Cabinet drop}} - 6$ "
$\overline{\text{Cabinets} - 1/8}$ " huck bolted aluminum
<u>Cargo bay walls</u> – $1/8$ " aluminum
Wheel wells $-1/8$ " aluminum
<u>Main sills</u> -5 " x 3" aluminum heavy-wall tubing
Cross sills -3 " x ¹ /4" aluminum channel
<u>Flooring</u> – 2" x 6" #1 Fir T&G treated decking
<u>Doors</u> $- 1/8$ " aluminum with $1/8$ " glue bonded aluminum hat section stiffeners
<u>Shelving</u> $- 1/8$ " aluminum that are adjustable in 2" increments
<u>Hinges</u> – Polished stainless steel
Handles – Polished stainless steel
Latching – 3-point stainless steel
<u>Door retainers</u> – Stainless steel door springs that lock into position
<u>Cabinet venting</u> – Bottom venturi's with drain holes to remove moisture build-up
Door seals – Rubber bulb seals that are glued into a u-shaped moulding
<u>Drip mouldings</u> – Glue bonded aluminum gutters that channel water away from the doors
<u>Wiring</u> – Watertight electrical relay box with master switches, Weatherpak connectors,
and continuous protective loom
Interior ceiling lights – Individual switches on lights with master switch
<u>Interior door lights</u> - Individual switches on lights with master switch, lights can be
swivelled 180 degrees
Exterior floodlights – Bosch 8" halogens with individual switches on lights and master
switch, lights can be rotated 360 degrees and tilted 180 degrees
<u>Running Lights</u> – Rubber mounted LED's
<u>Warranty</u> – 3-year structural, 3-year limited paint, and 5-year paint fade
<u>Paint protection</u> – 3M vinyl coatings on cabinet front, bottom, and wheel well edges
-3M rubberized wheel well coating
-Hippo Liner coated bumper
-Aluminum diamond plate bonded to the cabinet fronts
<u>Body finish</u> – Fully body worked for a smooth exterior with no seams or weld joints
<u>Paint</u> – White PPG Delfleet polyurethane
<u>1 and</u> – while 110 Demeet poryuremane
Brutus Body Specifications
Brutus Body Specifications

Driver side #1 – 60"H x 36"W x 24"D

- 1-Vertical steel door
- 1-Steel toolbox tray with 500 lb roller bearing sliders and locking latch
- 1-Aluminum bookshelf
- 1-Ceiling light

Driver side #2 – 60"H x 20"W x 24"D 1-Vertical steel door 3-Aluminum shelves 1-Door light

Driver side #3 – 33"H x 26"W x 24"D 1-Vertical steel door 2-Aluminum shelves 1-Door light

Driver side #4 – 51"H x 24"W x 22"D 1-Vertical steel door 1-Aluminum drip tray with drain hose 1-Hook for crane controller and cable (front wall)

Passenger side #1 – 60"H x 30"W x 24"D
1-Vertical steel door
2-Bottle holders with wear pads (front wall)
3-Gear hooks (1 rear wall, 2 back wall)
4-Vertical bar holders with tie down tabs (rear wall)
1-Stainless steel vent (above bottles)

Passenger side #2 – 60"H x 26"W x 24"D 1-Vertical steel door 3-Aluminum shelves 1-Door light

Passenger side #3 – 33"H x 26"W x 24"D 1-Vertical steel door 2-Aluminum shelves 1-Door light

Passenger side #4 – 22"H x 24"W x 22"D 1-Vertical steel door -Under deck cabinet

<u>Cargo bay - 82"D x 50"W x 39"H</u> (6" raised roof)

1-Flip up aluminum roof system with gas cylinders, stainless latching, and two removable aluminum rear panels

Rear deck – 50"D x 98"W

1-6" steel tubing tailgate with plastic covered drop chains, adjustable zinc plated latches, and hinges with grease nipples and brass inserts

2-6" steel tubing side railings

4-Zinc plated rotating d-ring tie downs (6,000 lb capacity each)

Misc. features

2-Rear mud flaps

1-Aluminum grab handle with rubber grips (crane pedestal)

4-Bosch 8" rooftop swivel halogen floodlights

1-7"L smooth steel step bumper with Hippo Liner coating

2-Vertical bumper vice receivers

1-Rubber mounted step